



Copperhead SoloShot™ Extra High Strength

Part# (1245*-EHS-)**

***= Color- B=Blue, G=Green, Y=Yellow, P=Purple, R=Red,
B=Black, N=Orange**

****=Spool Size- 500', 1000', 2500'**

Tracer wire for directional drilling/boring shall be a (12 AWG) extra-high-strength copper-clad steel conductor (EHS-CCS), insulated with a 45 mil, high-density, high molecular weight polyethylene (HDPE) insulation, and rated for direct burial use at 30 volts. EHS-CCS conductor must be a 21% conductivity for locating purposes, Break load will be 1150# minimum. HDPE insulation shall be RoHS compliant and utilize virgin grade material. Insulation color shall meet the APWA color code standard for identification of buried utilities. Tracer wire shall be Copperhead™ SoloShot™ Extra High Strength, EHS-CCS HDPE 45 mil insulation or Pre-approved equal and made in the USA.



UTILITY SUPPLY CORP.

USC WEST: 101-26921 Gloucester Way • Langley, BC • V4W 3Y3 • Phone: (855) 381-2146 • Fax: (604) 381-2147

USC EAST: 43 McBrine Place • Kitchener, ON • N2R 1E7 • Phone: (855) 748-4300 • Fax: (866) 615-0561

www.usccanada.com