



UTILITY SUPPLY (WEST) CORP.

#101-26921 Gloucester Way Langley, BC V4W 3Y3
Phone: 1-855-381-2146 Fax: 1-604-381-2147 www.usccanada.com

PETROWRAP LT - LOW TEMPERATURE

ANTI-CORROSION TAPE

PRODUCT DATA SHEET

DESCRIPTION

Petrolatum based with anti corrosion agents bonded to a specially woven fabric provides uniform thickness and strength. PetroWrap LT is engineered for low temperature applications in that it stays pliable in low temperatures.

USE

PetroWrap LT Anti Corrosion Tapes are cold applied over metal to provide long term corrosion protection to pipes, flanges, valves, hydraulic fittings, pier pilings, etc. PetroWrap LT can be used above ground, underground or underwater.



PetroWrap LT can be applied on already rusted surfaces or wire brushing can be done. Once applied, PetroWrap LT Tape is ready for service and provides many years of maintenance free protection from water, salt, alkalis, acids and caustics. PetroWrap LT AC Tape will not crack, peel or harden and is completely non-toxic and non-polluting.

PetroWrap LT is not recommended where exposure to strong solvents is likely.

TECHNICAL SPECIFICATIONS

Service Temp	-50° C to 70° C	Elongation	49%
	(-50° F to 158° F)	Dielectric Strength	193
Application Temp	-10° C to 50° C	Flash Point	629° F
Colour	Green / Brown	Water Vapour Transmission	.01
Thickness	1.15mm - 46mm	Width Deviation	-1
Cone Penetration @ 25° C	0.24	Thickness of Tape	53 mils
Drop Melting Point	163 ° F	Petrolatum Wax by Weight	57%
Breaking Strength	45.6		